

NQA04

4 Tons air -cooled
portable chiller





4.0 tons of cooling capacity
50°F set point
95°F condenser air inlet
3 hp coolant pump designed for 11 gpm at 56 psi
WARRANTY: AS IS
CONDITION: FAIR
VOLTAGE 575/3/60

Every NQ Series Portable Chiller comes standard with the following features:

- Nonferrous water circuit with stainless steel pump and evaporator protects against corrosion
- Reservoir low level alarm protects the pump from damage caused by operating dry
- 3-phase power monitor protects the compressor from damage caused by poor main power quality
- Air inlet filters keep dirt out of the unit for optimum performance and reduced maintenance
- Compressor anti-cycle timer protects against premature compressor failure under low-load conditions
- Supply and return temperature displays for easy process fluid temperature monitoring

Options

Alarm horn with alarm dry contact Alerts operator of any alarm condition; dry contact closes for remote alarm capability	Included
Main disconnect switch Built-in power lock-out (rotary non-fused)	Included
Upsize pump Larger 3 hp pump provides increased supply pressure	Included
C-UL508A industrial control panel Provides a C-UL508A labeled control enclosure and motor branch circuit protection	Included

Demandez une soumission pour l'équipement et l'installation par nos techniciens !

LUTEK PLASTIQUE EQUIPEMENT TEL. 514-421-8963